

Motori serie STANDARD AC

Classe di rendimento IE2 - high efficiency

Isolamento classe F - Protezione IP54
Servizio continuo S1 - Ventilazione superficiale esterna

Tipo 63 - 132 Carcassa alluminio V 230/400 Hz 50
Tipo 160 - 250 Carcassa ghisa V 400/690 Hz 50

	kW	A V 400 Hz 50	Nm	cos φ	rend η%	J kgm ²	Peso Kg
80A2	0.75	1.8	2.5	0.78	78	0.00039	8.4
80B2	1.1	2.6	3.7	0.78	80	0.00051	9.5
90S2	1.5	3.3	5	0.81	82	0.00093	12.3
90L2	2.2	4.6	7.4	0.82	84	0.00115	15
100L2	3	6.2	9.8	0.84	85	0.00211	19.7
112M2	4	8.4	13.2	0.80	86	0.00317	25.7
132SA2	5.5	11	18.2	0.83	87	0.00744	36.5
132SB2	7.5	14.2	24.7	0.86	89	0.00910	42.5
160MA2	11	20.4	36	0.87	90	0.0257	81
160MB2	15	27	49	0.88	91	0.0570	118
160L2	18.5	32	60	0.92	91	0.0670	134
180M2	22	38	72	0.91	92	0.1050	165
200LA2	30	51	97	0.93	92	0.1270	195
200LB2	37	64	120	0.90	93	0.1925	255
225M2	45	76	146	0.92	93	0.2200	290
250M2	55	94	180	0.90	94	0.3750	360

	kW	A V 400 Hz 50	Nm	cos φ	rend η%	J kgm ²	Peso Kg
80B4	0.75	1.9	5.2	0.72	80	0.00167	9.5
90S4	1.1	2.6	7.4	0.75	82	0.00168	12.4
90L4	1.5	3.4	10.2	0.78	83	0.00217	14.5
100LA4	2.2	4.7	14.5	0.80	85	0.00335	18.5
100LB4	3	6.4	20	0.79	86	0.00463	21.4
112M4	4	8.5	26.7	0.79	87	0.00957	28.4
132S4	5.5	11	36.8	0.82	88	0.01803	42
132M4	7.5	14.3	49.2	0.85	89	0.02218	52.5
160M4	11	21.2	72	0.84	90	0.0350	92
160L4	15	28	98	0.85	91	0.0780	120
180M4	18.5	34.6	121	0.84	92	0.0900	136
180L4	22	41	143	0.84	92	0.1375	170
200L4	30	55	195	0.85	93	0.1675	200
225S4	37	66	242	0.87	93	0.2750	270
225M4	45	80	295	0.87	94	0.3130	300
250M4	55	97	355	0.88	94	0.5250	375

	kW	A V 400 Hz 50	Nm	cos φ	rend η%	J kgm ²	Peso Kg
90S6	0.75	2.2	7.6	0.65	76	0.00322	12
90L6	1.1	2.9	11	0.70	79	0.00425	14.3
100L6	1.5	3.7	15.2	0.73	80	0.00624	19
112M6	2.2	5.2	22	0.74	82	0.01125	30
132S6	3	6.5	30	0.80	84	0.01790	40
132MA6	4	8.5	40	0.81	85	0.02320	46.4
132MB6	5.5	11.4	55	0.82	86	0.04290	52.5
160M6	7.5	15	75	0.83	88	0.0530	86
160L6	11	21.6	110	0.84	89	0.1125	114
180L6	15	30	148	0.80	90	0.1450	136
200LA6	18.5	35	181	0.84	91	0.2280	175
200LB6	22	41.5	217	0.84	91	0.2670	200
225M6	30	54	295	0.87	92	0.4430	265
250M6	37	65.4	360	0.88	93	0.8250	360